TECHNICAL DATA SHEET



issued: August 1, 2016



Finawax S

Anti-block (Stearamide)

CAS No. 124-26-5

EINECS # 204-693-2

PHYSICAL PROPERTIES

FASTNESS PROPERTIES None

Warpage

PARTICLE SIZE

Microbeads 400-600 µm

Density g/cm³

Melting Point 102°C +/-5 / 215°F +/-9

197°C / 387°F Flash Point

Boiling Point 408°C / 766°F

Acid Value 1.0 Maximum Iodine Value 1.0 Maximum

Amine Purity % 98 - 100 Solubility in Water Insoluble

Moisture Content % 0.25 Maximum Gardner Color 2.0 Maximum Bio Based Content Vegetable

APPLICATION PROFILE

Solvent Flexo	Water Flexo	Offset	Screen	Gravure	UV
•				\Diamond	\Diamond

LEGEND

- recommended

Disclaimer:

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we assume no obligation, express or implied, or liability for the use obligation, express or implied, or liability for the use of or reliance on the information and data provided. The information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

GLENDALE HEIGHTS, IL 60139