TECHNICAL DATA SHEET PLASTICS

issued: August 1, 2016



Akapearl 111

Silver white rutile pearlescent pigment with a average $<15 \, \mu m$ particle size. (Blend)

Pearlescent Pigment 18282-10-5

CICN No. 77891 - EINECS # 310-127-6 / 236-675-7 / TiO2 242-159-0

PHYSICAL PROPERTIES FASTNESS PROPERTIES FASTNESS PROPERTIES ≈3.00 Heat Stability Mass °C Weatherability Mass Density g/cm³ 7-11 Heat Stability Tint °C 300+ Weatherability Tint 7-8 Oil Absorption % 70-90 Light Stability Mass 7-8 Migration None Light Stability Tint 7-8 Warpage None

APPLICATION PROFILE

Film	Wire & Cable	Injection Mold	Fiber	Com- pounding	Blow Molding	Roto Molding	Sheet Extrusion	Pipe Extrusion

LEGEND

- recommended

PES

REGULATORY

FDA	AP(89) 1	Mercosur 23/04	ASTM 963	EN 71/III	Mercosur 108/2005 & 369/2007	RoHS II	SVHC Compilant	Propo- sition 65		
\Diamond	۵	۵	۵	۵	۵	۵		۵		

RESIN TYPE

ABS	ASA	CA/CP/ CAB	EVA	IONOMER	PA	PC	PE	PP	PS	PBT
۵	•	۵	۵		۵	۵		۵	۵	۵
PET	POM	PPO	PUR	PVC	PMMA	SAN				
	Α	A	A		Α	A				

SPECIAL REMARKS

FDA use 3% Max in plastic!

Disclaimer:

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we assume no obligation, express or implied, or liability for the use obligation, express or implied, or liability for the use of or reliance on the information and data provided. The information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.

GLENDALE HEIGHTS, IL 60139