# TECHNICAL DATA SHEET PLASTICS





# Akahue Phthalo Green

Clean yellow shade Cu-Phthalo green with excellent overall properties (Phthalocyanine)

Pigment Green 7 CAS No. 1328-53-6 CICN No. 74260 EINECS # 215-524-1

#### PHYSICAL PROPERTIES FASTNESS PROPERTIES FASTNESS PROPERTIES

Density g/cm <sup>3</sup>	1.66	Heat Stability Mass °C	300	Weatherability Mass	7-8
рН	6-8	Heat Stability Tint °C	315	Weatherability Tint	7-8
Oil Absorption %	35-45	Light Stability Mass	7-8	Migration	None
		Light Stability Tint	7-8	Warpage	Distinct

#### **APPLICATION PROFILE**

Film	Wire & Cable	Injection Mold	Fiber	Com- pounding	Blow Molding	Roto Molding	Sheet Extrusion	Pipe Extrusion
<b>6</b>		<b>6 6 0</b>				۵		

## **LEGEND**

recommended

♦ partially recommended

FDA	AP(89) 1	Mercosur 23/04	ASTM 963	EN 71/III	Mercosur 108/2005 & 369/2007	RoHS II	SVHC Compilant	Proposition 65
۵	•	۵	۵	۵	۵	۵	۵	<b>6</b>

#### **RESIN TYPE**

**REGULATORY** 

KLOIN TITL											
ABS	ASA	CA/CP/ CAB	EVA	IONOMER	PA	PC	PE	PP	PS	PBT	PES
۵	۵	۵	۵	۵	۵	۵	۵	۵	۵	۵	۵
PET	POM	PPO	PUR	PVC	PMMA	SAN					
6		•	•								

## Disclaimer:

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we assume no obligation, express or implied, or liability for the use obligation, express or implied, or liability for the use of or reliance on the information and data provided. The information is furnished upon condition that the person receiving it shall make their own determination of the suitability of the material for their particular purpose.